

EXEMPLES : BOX STAY WIRE

Description : Flat wire for stitching cartons and boxes.

Steel : 0,06 to 0,10 % carbon.

Tensile : 690 to 990 N/mm².

Finish : - Electro-galvanised, as per international standards.
- Liquor finish.



Size range :

MAIN STANDARDS

Larges sizes	Medium sizes	Small sizes
2,50 mm x 0,60 mm 2,50 mm x 0,50 mm 1,93 mm x 0,95 mm	1,80 mm x 0,60 mm 1,50 mm x 0,50 mm	0,90 mm x 0,60 mm 0,80 mm x 0,50 mm

Tolerances : width : $\pm 0,03$ to $\pm 0,05$ mm.
thickness : $\pm 0,01$ to $\pm 0,02$ mm.

Packaging : - Spool from 5 to 20 Kg.
- Reels of 150 Kg.
- Other packaging on special request.

Type	SPOOLS				REELS
	AM 5	BP 4	25 LB	AM 20	RGP 150
Weight of wire (Kg)	4,5	4,5	11,3	18	145
Ø Flange (mm)	150	155	226	240	560
Ø Inside dia (mm)	67	18,5	67,5	97	56
Ø Core dia (mm)	70	68,5	72	103	296
Height (mm)	50,5	64	60,5	96	204

Please note all weights shown are approximate, and issued for guidance only. All measurement are metric.

Unwinding : Static. Unwinding systems are available on request.

Important characteristics : It is recommended to specify the diameter of your wire requirements in mm.

CONFLANDEY reserves the right to modify any of the above details in the pursuit of improvements in quality and service.

CONFLANDEY INDUSTRIES

3 RUE DU CHATEAU AMONCOURT - BP 21 70170 PORT SUR SAONE - FRANCE

Tél. : 33 (3) 84.91.38.38 - FAX : 33 (3) 84.91.47.04

contact@conflandey-industries.com