

EXAMPLES : FENCING WIRE

Description : Round wire for the manufacturing of chain-link fencing and netting.

Steel : 0,03 to 0,80 % carbon.

Tensile strenght : 400 from 1 600 N/mm².

Coating : - Bright wire - uncoated
- Galvanised wire, light, ommercial or as per international standards.

Diameter : 1,50 to 6 mm.

Tolerances : ± 0,03 mm for Ø ≤ 1,90 mm.
± 0,05 mm for Ø > 1,90 mm.

Packaging : Orbit wound coils from 350 to 1 100 Kg.



	ORBIT WOUND COILS
Type	PC
Weight of wire (Kg)	800 / 1 100
Ø O.D. (mm)	800
Ø I.D. (mm)	350 / 400
Height (mm)	860

Please note all weights shown are approximate, and issued for guidance only. All measurement are metric.

Unwiding : Static. Unwinding systems are available on request.

Important characteristics : It is recommended to specify the diameter of your wire requirements in mm.

CONFLANDEY reserves the right to modify any of the above details in the pursuit of improvements in quality and service.

CONFLANDEY INDUSTRIES

3 RUE DU CHATEAU AMONCOURT – BP 21 70170 PORT SUR SAONE - FRANCE

Tél. : 33 (3) 84.91.38.38 - FAX : 33 (3) 84.91.47.04

contact@conflandey-industries.com