

EXEMPLES : HOSE WIRE

Description : Bright or galvanised wire for hose armouring.

Steel : 0,06 to 0,82 % carbon.

Tensite strenght : 600 to 2000 N/mm².

Coating : - Electro-galvanised.

- Liquor finish.
- Coppered
- Bright

Diameter : 0,70 to 3 mm.

Tolerance : 0,01 to 0,03 mm according to wire diameter

Packaging : - Reels from 400 to 1400 Kg.

- Spools FCD type from 250 to 500 Kg.
- Orbit wound coils from 250 to 1000 Kg.
- Pay-off pack drums.



	Spools FCD	Reels			Pay-off pack drums	Orbit wound coils
Type	BFCD	R 400	R 1400	Type	C780	PC
Weight of wire (Kg)	250 / 500	510	1400	Weight of wire(Kg)	200	250 / 1000
Ø Flange (mm)	760	750	1010	Ø outside dia. (mm)	501	800
Ø Inside dia. (mm)	33 / 43	80	80	Ø Inside dia. (mm)	322	350 / 400
Ø Core dia. (mm)	440	472	80		-	-
Height (mm)	280 / 315	540	699	Height (mm)	755	300 / 900

Please note all weights shown are approximate, and issued for guidance only. All measurement are metric.

Unwinding : Dynamic or static. Unwinding systems are available on request.

Important characteristics : It is recommended to specify the diameter of your wire requirements in mm.

CONFLANDEY reserves the right to modify any of the above details in the pursuit of improvements in quality and service.

CONFLANDEY INDUSTRIES

3 RUE DU CHATEAU AMONCOURT - BP 21 70170 PORT SUR SAONE - FRANCE

Tél. : 33 (3) 84.91.38.38 - FAX : 33 (3) 84.91.47.04

contact@conflandey-industries.com