

## EXEMPLES : PAPER CLIP WIRE

**Description :** High gloss round wire suitable for the manufacturing of paper clips.

**Steel :** 0,06 to 0,18 % carbon.

**Tensile strength :** 690 to 1 080 N/mm<sup>2</sup>.

**Coating :** - Electro-galvanised as per international standards.

- Liquor finish.

This wire is specially treated to provide the smoothest possible surfaces for high speed feeding.



**Diameter :** 0,80 to 1,80 mm.

**Tolerances :** ± 0,005 to ± 0,01 mm according to wire diameter.

**Packaging :** - Reels from 400 to 1 000 Kg.

- Pay-off pack drums of 220 Kg each (4 drums per pallet).

Type	REELS			PAY-OFF PACK DRUMS
	RP 400	RP 500	RP 1000	
Weight of wire (Kg)	480	480	980	220
Ø Flange (mm)	750	600	1 010	515
Ø Inside dia. (mm)	80	80	80	/
Ø Core dia. (mm)	472	360	637	325 chimmey
Height (mm)	542	702	539	760

Please note all weights shown are approximate, and issued for guidance only. All measurement are metric.

**Unwinding :** Dynamic or static. Unwinding systems are available on request.

**Important characteristics :** It is recommended to specify the diameter of your wire requirements in mm.

CONFLANDEY reserves the right to modify any of the above details in the pursuit of improvements in quality and service.

## CONFLANDEY INDUSTRIES

3 RUE DU CHATEAU AMONCOURT - BP 21 70170 PORT SUR SAONE - FRANCE

Tél. : 33 (3) 84.91.38.38 - FAX : 33 (3) 84.91.47.04

[contact@conflandey-industries.com](mailto:contact@conflandey-industries.com)