

## EXEMPLES : PRINTERS WIRE

**Description :** Round wire for stitching magazines, regular publications, books and various other leaflets.

**Steel :** 0,06 to 0,10 % carbon.

**Tensite strength:** between 840 and 1 100 N/mm<sup>2</sup>.  
Other tensite available on request.

**Coating :** Electro-galvanised.

**Diameter :** 0,46 - 0,50 - 0,55 - 0,60 - 0,65 - 0,70 - 0,80 - 0,90 – 1,00 mm

**Tolerances :** ± 0,005 mm.

**Packaging :** Spools from 3 to 100 Kg.



	Spools							
Type	BP 3	B 3	BP 4	B 6	BS 15	BB 20	BB 35	MP100
Weight of wire (Kg)	2,5	3	4,5	7	17	18,5	32	100
Ø Flange (mm)	147	140	155	161	300	202	255	355
Ø Inside dia. (mm)	18	16,5	18,5	16,5	52	32	33	127
Ø Outside dia.(mm)	57	90	68,5	89	212	110	118	224
Height (mm)	49	90	64	120	100	179	166	355

Please note all weights shown are approximate, and issued for guidance only. All measurement are metric.

**Unwinding :** Unwinding systems are available on request.

**Important characteristics :** It is recommended to specify the diameter of your wire requirements in mm.

CONFLANDEY reserves the right to modify any of the above details in the pursuit of improvements in quality and service.

## CONFLANDEY INDUSTRIES

3 RUE DU CHATEAU AMONCOURT - BP 21 70170 PORT SUR SAONE - FRANCE

Tél. : 33 (3) 84.91.38.38 - FAX : 33 (3) 84.91.47.04

[contact@conflandey-industries.com](mailto:contact@conflandey-industries.com)